



COOLPIX

At the heart of the image



- 10.0 megapixels
- 3.5x zoom
- 2.5-inch LCD
- VR image stabilization
- ISO 3200* capability
- External flash and converter lens

* ISO 3200 is available only for image sizes of 5M (2592 x 1944) or smaller.



COOLPIX P5000

www.nikon-coolpix.com

Quality and performance discerning photo lovers deserve.

VR image stabilization

Optical lens shift VR (Vibration Reduction) compensates for camera shake to prevent blur and produce clearer, sharper results in lower lighting or unsteady conditions. The benefits of full-time VR also extend to faster framing on the monitor and smoother action in movies.



10.0 megapixels of pure imaging power

That's plenty of sharp resolution to capture the finest details, crop creatively and

produce beautiful enlargements. Optimizing performance and color reproduction is an advanced new image-processing engine. And the quality optics of a 36-126mm Zoom-Nikkor lens (equivalent with 35mm format picture angle) maximizes compositional freedom.

Advanced shooting modes (P, S, A and M)

The new improved Mode dial provides quick access to greater personal control over camera operation and the unlimited creative possibilities offered by Programmed Auto [P], Shutter-priority Auto [S], Aperture-priority Auto [A], and Manual [M] exposure modes.



System expandability



Optional Wide-angle and Telephoto Converter lenses further extend focal and creative range, as does a built-in accessory shoe that supports Nikon's advanced i-TTL flash control for

external flashes, including the Speedlight SB-400, SB-600 and SB-800.

ISO 3200 capability

Extended light sensitivity range of ISO 64 to ISO 3200* and the new image-processing engine's ability to preserve high image quality at high ISO settings provide new opportunities to shoot more effectively in lower lighting conditions.

* ISO 3200 is available only for image sizes of 5M (2592 x 1944) or smaller.

Other features

- Optical viewfinder
- Magnesium alloy front panel
- 2.5-inch 230,000-dot LCD monitor with wide viewing angle
- Image optimization
- Anti-Shake mode, High-Sensitivity mode
- Distortion control*
- Face-priority AF
- In-Camera Red-Eye Fix
- D-Lighting

*When used with optional Wide-angle Converter WC-E67.



Nikon COOLPIX P5000 Specifications

Effective pixels:	10.0 million
Lens:	3.5x Zoom-Nikkor; 7.5-26.3mm (35mm [135] format picture angle: 36-126mm); f/2.7-5.3; 7 elements in 6 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 504mm)
Focus range (from lens):	30cm (1 ft.) to infinity (∞) [W], 70cm (2 ft. 4 in.) to infinity (∞) [T]; Macro close-up mode: 4cm (1.6 in.) to infinity (∞) [W], 40cm (1 ft. 4 in.) to infinity (∞) [T]
Monitor:	2.5-in., 230,000-dot, wide viewing angle TFT LCD with anti-reflection coating
Storage media:	Internal memory (approx. 21 MB), SD memory cards
ISO sensitivity:	ISO 64, 100, 200, 400, 800, 1600, 2000, 3200, Auto (auto gain ISO 64-800)
Power sources:	Rechargeable Li-ion Battery EN-EL5 (supplied), AC Adapter EH-62A (optional)
Battery life:	Approx. 250 shots with EN-EL5 battery (based on CIPA standard)
Dimensions (WxHxD):	Approx. 98 x 64.5 x 41 mm (3.9 x 2.5 x 1.6 in.) excluding projections
Weight:	Approx. 200 g (7.1 oz.) without battery and SD memory card

PictureProject System Requirements

OS: **Macintosh:** Mac® OS X version 10.3.9, 10.4.x
Windows: Windows® Vista (32bit), Windows® XP Home Edition/Professional, Windows® 2000 Professional pre-installed models

Note: CD-ROM drive required for installation. Only built-in USB ports are supported

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh® and QuickTime® are either registered trademarks or trademarks of Apple Computer Inc. in the United States and/or other countries. The SDHC logo is a trademark. PictBridge is a trademark. D-Lighting technology is provided by Apical Limited. Products and brand names are trademarks or registered trademarks of their respective companies. The FotoNation logo is a trademark. Image on LCD shown in this brochure is simulated. Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. February 2007 ©2007 NIKON CORPORATION



WARNING TO ENSURE CORRECT USAGE, READ MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT. SOME DOCUMENTATION IS SUPPLIED ON CD-ROM ONLY.



NIKON CORPORATION

Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku
 Tokyo 100-8331, Japan
<http://nikonimaging.com/>

Nikon Hong Kong Ltd. Suite 1001, 10/F Cityplaza One, 1111 King's Road, Taikoo Shing, Hong Kong www.nikon.com.hk
Nikon Singapore Pte. Ltd. No. 80 Anson Road, Fuji Xerox Towers, #10-01/02, Singapore 079907 www.nikon.com.sg
Nikon (Malaysia) Sdn. Bhd. 11th Floor, Block A, Menara PKNS, No. 17, Jalan Yong Shook Lin, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia www.nikon.com.my
NIKON AUSTRALIA PTY LTD. Unit F1, Lidcombe Business Park, 3-29 Birnie Avenue, Lidcombe NSW 2141, Australia www.nikon.com.au