

COOLPIX





- 7.1 megapixels
- 3x zoom
- 2.5-inch LCD
- VR image stabilization
- ISO 1000 capability



COOLPIX S200

Slim, smart and raring to go.

Elegant aluminum finish body, 18.5mm slim

Packing sophisticated style, advanced functions and high performance into its ultra-slim design, the COOLPIX S200 fits comfortably in the hand and simplifies operation for greater fun with photography.

■ VR image stabilization

Compensating for the effects of camera shake to realize sharper results, Electronic VR (Vibration Reduction) frees you to enjoy capturing special moments without worrying about slight hand movements, particularly in lower lighting conditions or when zooming in for close-ups.

■ ISO 1000 capability

Light sensitivity range up to ISO 1000 allows the use of faster shutter speeds to avoid blurred results when shooting moving subjects or in locations with insufficient lighting. ISO sensitivity is automatically optimized in High-Sensitivity mode.



Other features

- Large 2.5-inch 153,000-dot LCD monitor with anti-reflection coating
- Face-priority AF finds and focuses on people's faces for consistently crisp results
- In-Camera Red-Eye Fix in-camera compensation for more natural flash portraits
- D-Lighting adds detail and optimizes exposure to rescue underexposed images



Nikan COOL BIV COOL Chasifications

Nikon COOLPIX S200 Specifications	
Effective pixels:	7.1 million
Lens:	3x Zoom-Nikkor; 6.3-18.9mm (35mm [135] format picture angle: 38-114mm); f/3.1-5.9; 6 elements in 5 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 456mm)
Focus range (from lens):	60cm (2 ft.) to infinity (∞), Macro close-up mode: 10cm (3.9 in.) to infinity (∞)
Monitor:	2.5-in., 153,000-dot, TFT LCD with anti-reflection coating
Storage media:	Internal memory (approx. 20 MB), SD memory cards
ISO sensitivity:	ISO 50, 100, 200, 400, 800, 1000, Auto (auto gain ISO 50-800)
Power sources:	Rechargeable Li-ion Battery EN-EL10 (supplied), AC Adapter EH-62D (optional)
Battery life:	Approx. 230 shots with EN-EL10 battery (based on CIPA standard)
Dimensions (WxHxD):	Approx. 91.5 x 56.5 x 18.5 mm (3.6 x 2.2 x 0.7 in.) excluding projections
Weight:	Approx. 125 g (4.4 oz.) without battery and SD memory card

PictureProject System Requirements

Macintosh: Mac® OS X version 10.3.9, 10.4.x OS:

Windows: Windows® Vista (32bit), Windows® XP Home Edition/Professional, CD-ROM drive required for installation. Only built-in USB ports are supported

Windows® 2000 Professional pre-installed models

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh® and QuickTime® are either registered trademarks or trademarks of Apple Computer Inc. in the United States and/or other countries. The SDHC logo is a trademark. P-Lighting technology is provided by Apical Limited. Products and brand names are trademarks or registered trademarks of their respective companies. The FotoNation logo is a trademark. Image on LCD shown in this brochure is simulated.

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. February 2007 ©2007 NIKON CORPORATION



Note:

















WARNING

TO ENSURE CORRECT USAGE, READ MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT. SOME DOCUMENTATION IS SUPPLIED ON CD-ROM ONLY.



NIKON CORPORATION

Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku Tokyo 100-8331, Japan http://nikonimaging.com/

Nikon Hong Kong Ltd. Suite 1001, 10/F Cityplaza One, 1111 King's Road, Taikoo Shing, Hong Kong www.nikon.com.hk Nikon Singapore Pte. Ltd. No. 80 Anson Road, Fuji Xerox Towers, #10-01/02, Singapore 079907 www.nikon.com.sg Nikon (Malaysia) Sdn. Bhd. 11th Floor, Block A, Menara PKNS, No. 17, Jalan Yong Shook Lin, 46050 Petaling Jaya, Selangor Darul Ehsan,

NIKON AUSTRALIA PTY LTD. Unit F1, Lidcombe Business Park, 3-29 Birnie Avenue, Lidcombe NSW 2141, Australia www.nikon.com.au