

Effective: June 2006



Six adapter plugs included for worldwide 110-240 volt power source.

Designation:	Kodak Rapid Charger Model K4500	
Dimensions:	L 110.5mm x W 66.7mm x H 30.5mm (excluding plug)	
Weight:	101g (excluding plug)	
Battery Size Application:	AA or KAA2HR	
Battery Type:	NI-MH	
Battery Count:	(2) AA or (1) KAA2HR size batteries	
Display Device:	Solid red:	Discharging
	Flashing yellow :	Charging
	Flashing green:	Charging complete
	Flashing red:	Error (remove battery from charger)
Charge Termination:	Delta volta detection	
	Peak voltage detection	
	Protection timer	
Input Voltage:	100-240 VAC 50/60 Hz, 9W	Power plug style: - - - -
Output -Charger Current:	DC 1200mA ±10%	
Charge Time: (Approx):	NI-MH AA (2300mAh) 120 minutes	NI-MH AA (1850mAh) 95 minutes
	NI-MH AA (2100mAh) 110 minutes	NI-MH AA (1600mAh) 85 minutes
Charge Protection:	1) Timer 2) Over voltage protection	
Compliance:	1) Safety: Complies with IEC 60335-1, IEC-60335-2	
	2) EMI: Complies with EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3	
Approvals:	UL, FCC, CE GS, C-Tick, KETI, CQC	

For more information, contact
Eastman Kodak Company
343 State Street
Rochester NY 14650-0811
1-800-242-2424
www.kodak.com/go/batteries

The Data in this publication represents product tested under the conditions specified. They do not represent standards or specifications which must be met by Eastman Kodak Company. Company reserves the right to change and improve product characteristics at any time.